


OF AD A045018



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS 1963

AFGL-TR-77-0145

MODIFICATION OF A SOLAR EUV SPECTROMETER

John F. McGrath Joseph P. Padur

Comstock & Wescott, Inc. 765 Concord Avenue Cambridge, Massachusetts 02138





31 July 1977

Final Report for Period 1 November 1975 - 30 June 1977

Approved for public release; distribution unlimited.

JC FILE COPY

AIR FORCE GEOPHYSICS LABORATORY
AIR FORCE SYSTEMS COMMAND
UNITED STATES AIR FORCE
HANSCOM AFB, MASSACHUSETTS 01731

Qualified requestors may obtain additional copies from the Defense Documentation Center. All others should apply to the National Technical Information Service.

UNCLASSIFIED SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered) READ INSTRUCTIONS REPORT DOCUMENTATION PAGE BEFORE COMPLETING FORM 2. GOVT ACCESSION NO. 3. PECIPIENT'S CATALOG NUMBER AFGL-TR-77-0145 Final 1 Nov 1975 TITLE (and Subtitle) MODIFICATION OF A SOLAR EUV SPECTROMETER 30 June 1977 -CONTRACT OR GRANT NUMBER(S) John F. McGrath Joseph P./Padur F19628-76-C-0041 Mul 9. PERFORMING ORGANIZATION NAME AND ADDRESS Comstock & Wescott, Inc. 10. PROGRAM FLEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 62101F 765 Concord Avenue 6688/0601 Cambridge, Massachusetts 02138 11. CONTROLLING OFFICE NAME AND ADDRESS REPORT DATE Air Force Geophysics Laboratory 31 July 1977 Hanscom AFB, Massachusetts 01731 13. NUMBER OF PAGES Monitor/Charles W. Chagnon/LKO 14. MONITORING AGENCY NAME & ADDRESS(If different from Controlling Office) 15. SECURITY CLASS. (of this poport) Unclassified 15a. DECLASSIFICATION DOWNGRADING SCHEDULE 16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited 17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) 18. SUPPLEMENTARY NOTES 19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Extreme Ultraviolet, Ultraviolet, Monochromators, Spectrometers, Spectrophotometers, Photometers, Instrumentation, Rockets, Detectors, Vacuum, Upper Atmosphere Physics, Solar Radiation, Ground Support Equipment (GSE), Electronics, Flight Electronics. 20 ABSTRACT (Continue on reverse side if necessary and identify by block number) This report describes the modification of a solar extreme ultraviolet double spectrometer (RM-60) for sounding rockets. This instrument is of the grazing-incidence grating spectrometer This report also covers the modification of the existing ground support equipment (GSE) as well as the auxiliary

experiment.

Tuditabih tesanist :

i

TABLE OF CONTENTS

1.	GENERAL				•		•													1
2.	RELATED	C	ONT	RAC	rs															3
3.	ROCKET	SP	ECT	ROMI	ETE	ER	NC		60	- B										5
	General Redesig Modific	gn	and	Fal	ori	ca	ti	or	1											556
	3.3.1 3.3.2 3.3.3 3.3.4	Bo El	tto: ect:	m De	eck Sp	c oec	tr	·on	net	er	٠	:	:	•	:		:	:	:	
3.4	Assembl	Lу																		8
	3.4.1 3.4.2 3.4.3	RM	-60	- B	(E)	Lec	tr	or	nic)										
3.5	Test ar	nd	Del	ive:	ry															14



LIST OF TABLES

TABLE	I																								12
Techni	ca	1	Ch	aı	a	cte	eri	st	i	cs	0	f	Ro	cke	et	Sp	e	eti	or	net	cei	. 1	Vo.	60-	B

LIST OF FIGURES

Figure 1	9
Figure 2	LI
Figure 3	15
Figure 4	16
Figure 5	17

1. GENERAL

This report covers the design, development, and engineering activities of Comstock & Wescott, Inc. in support of a research program of the Air Force Geophysics Laboratory (AFGL). The work discussed in this report covers the modification of spectrometer RM-60 to convert it from a rocket-borne instrument concentrating on plage areas of the sun to one measuring full disc solar fluxes.

The principal engineers on this contract were

Mr. John F. McGrath, Director of Mechanical Engineering, and

Mr. Joseph P. Padur, Project Physicist.

Work in the field of electronics, including the flight electronics and ground support equipment (GSE) modification, was subcontracted to TRI-CON Associates, Inc. and was conducted under the direction of Mr. Chester G. Kuczun and Mr. Robert S. Hills. Other technical contributors to the contract were Messrs. Charles W. Peterson, William F. Burke, and George W. Guay of Comstock & Wescott, Inc., and Messrs. Norbert F. Robertie and Timothy A. Doyle of TRI-CON Associates, Inc.

2. RELATED CONTRACTS

The following contracts have preceded the contract covered by this report:

AF19(604)-1097, 1954 to 1956. Contract concerned with development of a soft X-ray radiation source and an associated high vacuum system.

AF19(604)-1889, 1956 to 1959. Measurements of EUV and soft X-rays.

AF19(604)-5693, 1959 to 1961. Investigation of extreme ultraviolet solar radiation and clarification of role of photoelectron emission.

AF19(604)-7496, 1960 to 1963.

Development of a number of rocket and satellite monochromators and retarding potential detectors.

Specific reference is made to the Final Report AFCRL-64-773 of this contract.

An associated contract which ran concurrently with AF19(604)-7496 was AF19(628)-2975.

This was concerned with research into the photoemission properties of materials and with the investigation and development of various spectroscopic instruments.

AF19(628)-4317 was an extension of AF19(604)-7496.

Contract AF19(628)-5188 covered a further extension of this work.

Contract F19628-68-C-0239 covered an extension of the work performed under the former contract and preceded the work covered by this report.

Contract F19628-72-C-0048 covered a modification of a Double-Deck EUV Spectrophotometer.

Contract F19628-72-C-0254 covered design, development, and fabrication of a double spectrophotometer consisting of one grazing incidence and one normal incidence grating spectrophotometer.

Contract F19628-73-C-0253 covered design and fabrication of two double-deck solar extreme ultraviolet spectrometers.

Contract F19628-74-C-0002 covered design and fabrication of a normal-incidence extreme ultraviolet grating spectrometer.

Other contracts carried out by Comstock & Wescott in the field of space instrumentation, but not directly related to this contract, are:

AF19(628)-253 - Research directed toward Design of Instrumentation for Investigation of Aerospace by Rocket and Satellite Probe Techniques.

AF19(628)-4988 - Rocket and Satellite Probe Techniques.

F19628-68-C-0307 - Continuation of AF19(628)-4988.

F19628-72-C-0027 - Continuation of F19628-68-C-0307.

3. ROCKET SPECTROMETER NO. 60-B

3.1 General

The objective of this modification was to convert rocket spectrometer RM-60 (described in detail in AFGL-TR-76-0160) from a rocket-borne instrument concentrating on plage areas of the sun to one, RM-60-B, measuring full disc solar fluxes. The original instrument contained two scanning carriages covering the wavelength range of 55Å to 310Å in one deck and 220Å to 1220Å in the other deck. The modified instrument retained the coverage of 55Å to 310Å in the top deck but the bottom deck was changed to concentrate on four discrete spectral regions centered at a specific wavelength. The four center wavelengths were: 284Å, 630Å, 915Å, and 1206Å.

Some modifications also were carried out on the electronics of the auxiliary experiments of RM-60, namely, the electron spectrometer and the side-viewing photometer.

3.2 Redesign and Fabrication

In order to carry out the above requirements, some effort was afforded to redesign and fabrication of necessary components. It was necessary during the time period of this contract to investigate production problems with the CEM detector manufacturer, necessitating the purchase of new detectors for both decks of this instrument. These problems were enumerated in AFGL-TR-76-0160.

Some of the mechanical and electronics modifications listed below are dimensional changes of components thereby requiring replacement of some subassembly parts used in RM-60 whereas others are entirely new components. Where no reference is made to a specific component or assembly, it is then the same as used in RM-60. Reference therefore should be made to AFGL-TR-76-0160.

3.3 Modifications

3.3.1 Top Deck

- (a) Four new CEM detectors (purchase, test, wire, and assemble).
- (b) MgF_2 coating on the two shortest wavelength detector cones (those covering 50\AA 101\AA and 96\AA 159\AA).
- (c) Four .005" (.127mm) exit slits for calibration.
- (d) One .005" (.127mm) entrance slit for calibration.
- (e) One .002" (.0508mm) entrance slit for flight.
- (f) One entrance slit assembly mount.
- (g) One 5mm slit height limiter.
- (h) Rewiring of CEM units to amplifiers and harness.

3.3.2 Bottom Deck

- (a) Four new CEM detectors (purchase, test, wire, and assemble).
- (b) New carriage for four selected wavelengths.
- (c) New belt for carriage drive.
- (d) New limit switch assembly.
- (e) Four .005" (.127mm) exit slits.
- (f) One .002" (.0508mm) entrance slit.
- (g) One entrance slit assembly mount.
- (h) One 5mm slit height limiter.
- (i) Change step rate from 100 frames per second to 10 frames per second.
- (j) Add double step capability to circuit board.
- (k) Rewiring of CEM units to amplifiers and harness.

3.3.3 Electron Spectrometer

- (a) Construct two new electronics boards.
- (b) Rewiring of electronics to experiment.

3.3.4 Side Viewing Photometer


The electronics boards and detector assembly as an auxiliary experiment of RM-60 were removed from the original housing and relocated in another section of the rocket payload in RM-60-B without any electronics board changes.


3.4 Assembly

3.4.1 RM-60-B (Mechanical)

Eight new CEM detectors (two having MgF2 coated cones) were positioned into the stripped Kel-F holders from which the original eight detectors were removed. They were potted into place, assembled with and wired to their respective amplifiers and plateaued prior to assembly and wiring on their respective carriages. An optical alignment test was carried out on each deck, wherein the exit slits were adjusted parallel to their respective entrance slit prior to calibration. An internal assembly drawing, Figure 1, illustrates the design of the original instrument. Item 22 (Channeltron carrier assembly of bottom deck) has been replaced during this modification by the assembly illustrated in Figure 2.

Table I lists the technical characteristics of the modified instrument.









Figure 1. Internal As 5032 EUV Sp

9



APT MATER				1	TO VI	19 VI 100 (11 10 2032-0 10011 10 2							
HEXT ABST	UMD ON	- more	CTIVE FINISM	AMONS	3150	E 391							
	5032						SPAN JOE HE						
		MY. CW	M.	frank	773								
		- 63	NOT SCALE INS DRAWING	WHO TO		INTERNAL ASSEMBLY							
		DECT	MALS SE VALS ANGLES	CHICAED	INTER								
		7	MAYE V	G.W. GUAY	1973								
			ACE FINEA T	73-0253	244	BRIDGE MASSACHU	SETTS						
			SS OTHER LINE SPECIFIED	CONTRACT NO.		OCK & WESCOTT, INC.							
		-			STOPPIS	DENT HO.							
		men		ESCRIPTION	DENTIFY MO	PERCETOR	Coot IND						
		1	MONOCHROM	ATOR HOUSING	E 389		1 1						
		2	GUICE RAIL T	RAP	A 2307		1 1						
		3	BOC HO CAP	SCREW	*2-56WG g.		1 1						
		4	SOC HO CAP	SCREW	4-40UNC 4.5		1						
		5	SOC HO CAP &		8-320C.4U	ST ST							
		6	TAKE -UP PUL		C 500	-	1						
		7	BELT DRIVE		D 800	51. 5TL	-						
		-	BUTTON HO		16-32UNC 1:4	1							
		10		CARRIER (TOP DE	4-40UK	ST. STL	- 4						
		11	FLAT HD SCRE		C1227	-	-						
		12	BUTTON HD		16-32UNC	ST. STL	-						
		13	SOC HD CAP SO		6-32MC								
		14	GRATING MOL		C1225-1								
		15	SOC HO CAP S		4-40UNCX & LO		1						
		16	GRATING MOU		C 1225-2								
		17	CONNECTOR		DAM 155	ITT CALLON							
		18	PAN HO SCR	EW	4-40UNC = 1/2U	ST. ST_	1						
		18	HEX NUT		#4-40UNC	ST. ST.	1						
		20	BUTTON HO	SCREW	"2-56UNC# EL	ST. STL	1 13						
		21	GUIDE RAIL T	RAD	A 2655-1		1						
		122	CHANNELTRON CA	RRIER ASSY (BTM. O	00 0 799		1 1						

Figure 1. Internal Assembly Model 5032 EUV Spectrometer




Figure 2. Channeltron Carrier Assembly

TABLE I

TECHNICAL CHARACTERISTICS OF ROCKET SPECTROMETER NO. 60-B

Bottom Deck	. 0508 mm	$300~\ell/\text{mm}$ gold replica	.127 mm	4 СЕМ	284, 630, 915, 1206Å	30	.127 mm	3 sec	10 steps per sec (double step)	2.28 FWHM	5 mm
Top Deck	(.0508 mm (Flight) (.127 mm (Calibration)	1200 l/mm gold replica	(.0508 mm (Flight) (.127 mm (Calibration)	$^{\rm 4}$ CEM $^{\rm 6}$ (MgF $_{\rm 2}$ coated cones on two shortest wavelengths)	558 - 310R	1400	. 06096 mm	~ 140 sec	10 steps per sec	0.228 FWHM	5 mm
	Entrance Slit	Grating	Exit Slit	Detectors	Wavelengths Covered	Steps per Scan	Distance per step	Duration of Scan	Stepping Rate	Resolution	Slit Height Limiter

3.4.2 RM-60-B (Electronics)

The frame rate (or scan step rate) of the bottom deck was changed from 100 frames per second to 10 frames per second by adding a 10:1 frequency divider to the timer circuit of the motor drive/timer printed circuit card. The motor drive section of the same board was also modified to step the motor twice during each frame. A schematic of the updated motor drive/timer board is given in Figure 3. A timing diagram for the modified instrument is given in Figure 4.

3.4.3 Auxiliary Experiments

The auxiliary experiments originally built for RM-60 were used on RM-60-B. However, the analyzer voltage steps of the electron spectrometer were changed from the original ones and a new circuit board was required. The new step generator/drive schematic is illustrated in Figure 5. Since the electronics cards were mounted on top of the instrument in RM-60-B rather than in the detector assembly at the rear of the electronics package (RM-60), the five electronics boards were redesigned and incorporated into two newly constructed cards.

As mentioned previously, the photometer cards built for RM-60 were used for RM-60-B but were mounted with the photometer detector in a new rocket extension below the main instrument.

3.5 Test and Delivery

Prior to delivery to AFGL, a preliminary acceptance test was carried out at Comstock & Wescott. This test included the operation of the instrument with the GSE through all of the necessary bench functions. An addendum to the previous "Test and Acceptance Plan for RM-60" was submitted to AFGL to encompass the modification introduced into the operation of the instrument. The instrument was delivered to AFGL for further acceptance testing and calibration. No launch support services were supplied under this contract.




Figure 3. Schematic Motor Drive/Timer RM-60B




Figure 4. Timing Diagram RM-60B





Figure 5. Step Generator/Drive Electron Spectrometer



AD-A045 018

COMSTOCK AND WESTCOTT INC CAMBRIDGE MASS MODIFICATION OF A SOLAR EUV SPECTROMETER.(U) JUL 77 J F MCGRATH, J P PADUR

F/6 14/2

F19628-76-C-0041 AFGL-TR-77-0145 NL

UNCLASSIFIED

2 of 2 ADI AO45018








DUPUED 2

AD A045018



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

SUPPLEMENTAI

INFORMATION

AFGL-TR-77-0145 Final Report F19628-76-C-0041

MODIFICATION OF A SOLAR EUV SPECTROMETER
John F. McGrath
Joseph P. Padur

Errata

Delete the name of John F. McGrath from the cover and Block 7 of the DD Form 1473.

AIR FORCE GEOPHYSICS LABORATORY AIR FORCE SYSTEMS COMMAND UNITED STATES AIR FORCE HANSCOM AFB, MASSACHUSETTS 01731